



50" Stand-Type
Movable+Touchable
Made by **Foxconn**



5.8 cm slim body design



Preset commercial templates
for easy editing




Smart schedule playback

Simple and Delicate Design

- Portable Device
- Removable Wheel Brake
- Integrated Design of Power, Switch, Network
- Convenient Maintenance with door

Slim Appearance

- Large Size Panel and Display Area
- Mirrored Tempered Glass
- Excellent Image Quality
- External Network Port and Wi-Fi Antenna



Flexible Layout



Banking & Finance



Commercial Display



Communication System

50" Stand-Type Movable+Touchable Digital Signage

LCD Specifications	Panel Size	50"
	Type/technology	TFT Display with Backlight LCD module
	Visual Area (mm)	1095.84(H) X 616.41(V)
	Frame Rate	60Hz
	Color gamut	16.7M
	Backlight Module Technology	E-LED (lateral LED module)
	Resolution	1920 x 1080
	Brightness(Typical)	300 nits
	Dynamic Contrast	1,000,000 :1
	Contrast	5000:1
	View Angle	Horizontal: 176°/vertical: 176°
	Response Time (Typical)	9.5ms
	Orientation	Portrait
	Lifetime	30000Hrs
Touch Control Module	Touch Technology	Infrared Technology
	Multi-Touch Point	4 points
	Resolution	32767 x 32767T
	Accuracy	± 3mm
	Lifetime	Unlimited (theoretically)
	Responsive Time	<10ms
	Sweep Rate	100Hz
	Light Resistance	Excellent
	Protective Glass	4mm toughened glass
	Chips	Quad-core
System and I/O Interface	Flash	8 GB
	Memory	1 GB
	HDMI-out	1
	USB(USB2.0)	2
	Ethernet (Ethernet Network)	10/100 BASE-TX
	WIFI	802.11 b/g/n
	Micro USB	for debug
	Operating System	Android 4.4.2
	Speaker's Output Power	10W+10W
	Full / Partial Display	0
Software Function	Preset Commercial Templates for easy type-setting	0
	Programmed Display for display of different content in different time	0
	Programmed display, for timing switch	0
	Multi-media Image format	JPG, JPEG, PNG, MPG, MPEG
	Multi-media Video Format	AVI, WMV, MOV, MP4, DIVX, RMVB
	Brief Play	PPT/PPTX
	USB Update	0
	Network (point to point) update	0
	Preset digital billboard software	SignApps Express
	Software update	Software update Directly at terminal
Package list	Base	0
	Base screw	0
	Remote control + battery	0
	User manual (warranty card)	0
	Power cable	0
	Antenna	0
	Wheels	4
	Editing software CD	0
Others	Base Material	Galvanized steel sheet
	Remote Control Technique	Infrared remote control
	Power indication light (On/Off)	0
	Power Panel Specification	100-240V @ 50-60Hz
	Rated Power	110W
	Safety Certification	3C/BSMI
	Temperature	0~50°
	Humidity	20%~90% noncondensing
	Machine's Size (including Base)	1940mm x 690mm x 58mm
	Machine's Size (excluding Base)	1830mm x 690mm x 58mm
	Unit Weight (including Base)	62 Kg
	Unit Weight (excluding Base)	52 Kg
Cardboard Package Weight (including base)	71 Kg	

- สีผลิตภัณฑ์ที่แท้จริงอาจแตกต่างจากสีที่ปรากฏในเอกสารเล็กน้อย เนื่องจากกระบวนการพิมพ์
- รายละเอียดสินค้า อาจมีการเปลี่ยนแปลงโดยไม่ต้องแจ้งให้ทราบล่วงหน้า ค่าตัดสินโดยบริษัทฯ ถือเป็นที่สุด

10/2017

LENZO INTERTRADE CO., LTD
 292 Srinakarin Road, Huamark,
 Bangkapi, Bangkok 10240 Thailand.
 Tel:+66(0) 2375-2425-33
 Fax:+66(0) 2375-2434-5
 www.lensocom.com

CUSTOMER CARE CENTER

ศูนย์บริการลูกค้าสัมพันธ์

0 2855 8888

เวลาการทำงาน จันทร์ - เสาร์ 08.00-18.00 น.
 วันอาทิตย์หยุดทำการ